


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 102.49 lm/W
4 x LIMOLUX 560mm 1300lm 840 HV ADV5		I _{max} (cd)	413.4	S/MH (C0/180)	1.24	
NOMINAL POWER (W)		LOR (%)	100.0	S/MH (C90/270)	1.19	
RATED VOLTAGE (V)	220.0	TOTAL FLUX (lm)	1127.1	η UP,DN (C0-180)	0.0, 51.6	
NOMINAL FLUX (lm)	1127.12	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0, 48.4	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE (V)	230	η down (%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 7.250m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	403.8	404.3	407.5	408.4	405.3	404.7	400.6	398.8	0- 10	38.99	38.99	3.46,3.46
20	378.6	378.7	384.4	387.3	380.8	379.2	371.4	369.4	10- 20	110.9	149.9	13.3,13.3
30	342.5	339.1	346.4	351.1	342.2	339.5	328.7	327.0	20- 30	166.0	315.9	28,28
40	290.7	290.7	297.0	303.2	292.6	289.3	276.2	275.4	30- 40	197.2	513.1	45.5,45.5
50	232.1	231.0	239.8	246.8	235.2	231.6	217.4	220.1	40- 50	201.1	714.2	63.4,63.4
60	168.5	167.6	177.8	184.6	172.7	168.9	155.0	153.2	50- 60	179.1	893.3	79.3,79.3
70	102.9	102.7	113.1	119.7	106.8	104.7	90.93	88.94	60- 70	134.7	1028	91.2,91.2
80	41.93	42.97	52.46	57.53	44.41	43.41	33.77	31.48	70- 80	76.93	1105	98,98
90	0.7491	0.8086	6.466	8.892	0.9277	1.044	0.8462	0.9277	80- 90	22.15	1127	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 614.87 lm

%lum = 54.6%

%lamp = 54.6%

Conical surface Flux(120deg): 893.29 lm

%lum = 79.3%


%lamp = 79.3%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	558	864
80	685	857
75	783	899
70	854	938
65	912	977
60	956	1009
55	992	1035
50	1024	1059
45	1047	1080


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:FLX	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.308	.175	.055	.301	.172	.055	.288	.165	.053	.275	.159	.051	.264	.153	.049	
2.0	.290	.159	.049	.283	.156	.048	.272	.151	.047	.261	.146	.046	.251	.142	.045	
3.0	.268	.143	.043	.263	.141	.042	.252	.137	.042	.243	.133	.041	.234	.129	.040	
4.0	.247	.129	.038	.243	.127	.038	.233	.124	.037	.225	.121	.036	.217	.118	.036	
5.0	.229	.117	.034	.225	.115	.034	.216	.113	.033	.209	.110	.033	.202	.108	.032	
6.0	.212	.106	.030	.208	.105	.030	.201	.103	.030	.194	.101	.030	.188	.099	.029	
7.0	.198	.098	.028	.194	.097	.028	.188	.095	.027	.182	.093	.027	.176	.091	.027	
8.0	.185	.090	.025	.182	.089	.025	.176	.088	.025	.170	.086	.025	.165	.085	.025	
9.0	.173	.084	.023	.170	.083	.023	.165	.082	.023	.160	.080	.023	.156	.079	.023	
10.0	.163	.078	.022	.160	.077	.022	.156	.076	.021	.151	.075	.021	.147	.074	.021	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.172	.132	.098	.147	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.164	.114	.075	.141	.099	.065	.097	.068	.045	.056	.040	.027	.018	.013	.009	
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007	
5.0	.149	.091	.047	.128	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006	
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.047	.027	.012	.015	.009	.004	
8.0	.129	.069	.029	.111	.060	.025	.077	.042	.018	.045	.025	.011	.014	.008	.004	
9.0	.122	.064	.025	.106	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003	
10.0	.117	.060	.023	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm											
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED							WEIGHT:				
SPEC.:					DIM.:			SERIAL No.:			
MFR.: DARKON					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		12.4	13.9	12.6	14.1	14.3	12.5	14.1	12.8	14.3	14.5
	3H	13.8	15.2	14.1	15.5	15.7	14.1	15.5	14.4	15.7	16.0
	4H	14.4	15.7	14.7	16.0	16.2	14.8	16.1	15.1	16.3	16.6
	6H	14.8	16.0	15.1	16.3	16.6	15.3	16.5	15.6	16.8	17.1
	8H	14.9	16.1	15.2	16.4	16.7	15.5	16.7	15.8	17.0	17.2
	12H	15.0	16.1	15.3	16.4	16.7	15.6	16.8	16.0	17.1	17.4
4H	2H	13.0	14.3	13.3	14.5	14.8	13.1	14.4	13.4	14.7	14.9
	3H	14.6	15.8	15.0	16.1	16.4	14.8	16.0	15.2	16.3	16.6
	4H	15.3	16.4	15.7	16.7	17.0	15.6	16.7	16.0	17.0	17.3
	6H	15.8	16.8	16.2	17.1	17.5	16.3	17.2	16.7	17.6	17.9
	8H	16.0	16.9	16.4	17.2	17.6	16.5	17.4	16.9	17.8	18.1
	12H	16.1	16.9	16.5	17.3	17.7	16.7	17.5	17.1	17.9	18.3
8H	4H	15.6	16.4	16.0	16.8	17.2	15.8	16.7	16.3	17.1	17.5
	6H	16.2	17.0	16.7	17.4	17.8	16.6	17.4	17.1	17.8	18.2
	8H	16.5	17.1	16.9	17.5	18.0	17.0	17.6	17.4	18.0	18.5
	12H	16.6	17.2	17.1	17.6	18.1	17.3	17.8	17.7	18.3	18.7
12H	4H	15.6	16.4	16.0	16.8	17.2	15.9	16.7	16.3	17.0	17.5
	6H	16.3	16.9	16.7	17.4	17.8	16.7	17.3	17.1	17.7	18.2
	8H	16.6	17.1	17.0	17.6	18.0	17.1	17.6	17.5	18.1	18.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1127 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.4)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM	HE TYPE: HE	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	57	46	39	56	46	39	33
0.80	68	57	49	67	56	49	65	55	49	42
1.00	76	65	58	75	65	58	73	66	57	50
1.25	83	73	66	82	72	66	79	71	65	58
1.50	88	79	72	87	78	71	84	76	70	63
2.00	95	87	80	93	86	80	90	83	78	70
2.50	99	91	85	97	90	84	93	87	83	74
3.00	102	96	90	100	94	89	96	91	87	78
4.00	106	101	96	104	99	95	100	96	92	83
5.00	109	104	100	106	102	98	102	98	95	86
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 7.250m [K=1.0000]
Remarks:

AAI Figure

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:ALEX	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:240.04V I:0.0663A P:10.997W PF:0.6908 Freq:50.09Hz Lamp Flux:1127.12x1 lm		
NAME: BAY-KON_1195 x 295_THREDBO WHITE_YPP VL2 2MM HE TYPE:LED	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:
MFR.: DARKON	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	925
L_0~180 (75) av	799
L_0~180 (85) av	587
L_90~270 (65) av	900
L_90~270 (75) av	782
L_90~270 (85) av	618
L_45 (65) av	921
L_45 (75) av	810
L_45 (85) av	630

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:26 November 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 26 November 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 7.250m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:7.250m [K=1.0000]
Remarks:

```